## **AMENDMENTS TO THE CLAIMS**

The following claim set replaces all prior versions, and listings, of claims in the application:

- 1 14 (Cancelled)
- 15. (Currently Amended) A premixed liquid monopropellant which consists of an aqueous mixture of hydrogen peroxide, and ethanol, and water in an amount sufficient to render the monopropellant nondetonable and to maintain a flame temperature when ignited of about 2000°K or less.
- 16. (Previously Presented) The premixed liquid monopropellant of claim 15, wherein the hydrogen peroxide is present at a 70% concentration in water.
- 17. (Previously Presented) The premixed liquid monopropellant of claim 15, wherein the hydrogen peroxide is present in the mixture in an amount between 77% to 80%.
- 18. (Previously Presented) The premixed liquid monopropellant of claim 17, wherein the ethanol is present in the mixture in an amount between 12% to 20%.
- 19. (Currently Amended) The premixed liquid monopropellant of claim 18, wherein <u>hydrogen peroxide is present at a 70% concentration in water, and wherein an additional amount of water is present in the mixture in an amount of between 3% to 8%.</u>
- 20. (Currently Amended) A premixed liquid monopropellant which consists of 80% hydrogen peroxide having a concentration in water of 70%, 12% ethanol and 8% additional water.

MARTIN et al Serial No. 09/363,013 November 4, 2004

- 21. (New) The premixed liquid monopropellant of claim 15 or 20, which further consists of a solid oxidizer present as a solute in the liquid monopropellant.
- 22. (New) The premixed liquid monopropellant of claim 21, wherein the solid oxidizer is aminoguanidine nitrate, ammonium nitrate or ammonium dinitramide.